


Dual Inline Package 6pin type
of 400V load voltage

PHOTO DMOS RELAY AV40(H)(A)

1 From A




FEATURE

1. Continuous load current: Max. 130mA.
2. Load on resistance: Typ. 20Ω.
3. Loading voltage 400V DC or AC peak.
4. Off-state leakage current: 1μA.

TYPICAL APPLICATIONS

- Measurement and test equipment
- Telecommunications
- Security equipment
- Industrial machinery and equipment



1. LED Anode
2. LED Cathode
3. No Connect
4. MOSFET Drain
5. MOSFET Source
6. MOSFET Drain

Absolute maximum ratings (Ambient temperature 25 °C)

Item		Symbol	Value	Units	Not
Input	Continuous LED current	I_F	50	mA	
	Peak LED current	I_{FP}	1000	mA	f=100Hz, DC 1%
	LED reverse voltage	V_R	5	V	
	Input power dissipation	P_{in}	75	mW	
Output	Load voltage	V_L	400	V	DC or AC peak
	Load current	I_L	130	mA	AC & DC
	Peak load current	I_{peak}	300	mA	100ms(1 pulse)
	Output power dissipation	P_{out}	300	mW	
Total power dissipation		P_T	350	mW	
I/O isolation voltage		V_{iso}	3750	Vrms	RH 60, 1min
I/O isolation voltage(H)			5000	Vrms	RH 60, 1min
Operating temperature		T_{opr}	-40o +85	°C	
Storage temperature		T_{stg}	-40 to +100	°C	
Soldering temperature		T_{sol}	260	°C	10sec max.



RAPIDTEK PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay

Electrical specifications (Ambient temperature 25 °C)							
Item		Symbol	Min.	Typ.	Max.	Units	Condition
Input	LED forward voltage	V_F		1.2	1.5	V	$I_F=10\text{mA}$
	Operating LED current	I_{Fon}		0.8	5.0	mA	
	Recover LED current	I_{Foff}	0.1	0.35		mA	
	Recover LED voltage	V_{Foff}	0.5			V	
Output	On resistance	R_{on}		20.0	30.0	Ω	$I_F=10\text{mA}, I_L=100\text{mA}$
	Off-state leakage current	I_{leak}			1.0	μA	$V_L=\text{Rating}$
	Output capacitance	C_{out}		45		pF	$V_L=0\text{V}, f=1\text{MHz}$
Transmission	Turn on time	T_{on}		0.23	0.5	ms	$I_F=10\text{mA}, I_L=100\text{mA}$
	Turn off time	T_{off}		0.05	0.2	ms	
Coupled	I/O isolation resistance	$R_{I/O}$	10^9			Ω	DC 500V
	I/O capacitance	$C_{I/O}$		0.8	1.5	pF	$f=1\text{MHz}$

Circuit connections		
Item	Circuit	Remark
A Connections		AC & DC
B Connections		DC only
C Connections		DC only



RAPIDTEK
PHOTO DMOD RELAY


Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY


1 Form A Photo Relay

Reference data


Load current vs. Ambient temperature




On resistance vs. Ambient temperature




Turn on time vs. Ambient temperature




Turn off time vs. Ambient temperature




LED operate current vs. Ambient temperature




LED turn off current vs. Ambient temperature




LED forward voltage vs. Ambient temperature




Voltage vs. current characteristics of output at MOS portion




Off state leakage current vs. Load voltage characteristics




LED forward current vs. Turn on time characteristics



LED forward current vs. Turn off time characteristics



Applied voltage vs. Output capacitance characteristics




RAPIDTEK
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay

Taping specifications for surface mount devices



	B ₀ (mm)	F ₀ (mm)	W ₀ (mm)
Specification	9.4±0.1	7.5±0.1	16±0.1

Package	Part No.		Packing quantity	
	Tube packing	Tape & Reel packing	Tube	Tape & Reel
DPI6	AV40(H)	-	50pcs/1tube	-
SMD6	AV40(H)A	AV40(H)A-R1		1000 pcs

*H:Option



RAPIDTEK
PHOTO DMOD RELAY


Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>

PHOTO DMOS RELAY

1 Form A Photo Relay

Dimension


Recommended mounting pad



Unit:mm[inch]

Tolerance:±0.2[±0.007]

DIP




Unit:mm[inch]

Tolerance:±0.2[±0.007]

Marking

(Each photo MOS Relay shall be marked with the following information)



YY : Year, M : Monthly, W : Weeks

*H:Option



RAPIDTEK
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.
<http://www.rapidtek.net>