


Dual Inline Package 4pin type  
of 60V load voltage

# PHOTO DMOS RELAY AY6E (H)(A)

1 From A




## FEATURE

1. Continuous load current: Max. 200mA.
2. Load on resistance: Typ. 2.0Ω.
3. Loading voltage 60V DC or AC peak.
4. Off-state leakage current: 1μA.

## TYPICAL APPLICATIONS

- Measurement and test equipment
- Telecommunications
- Security equipment
- Industrial machinery and equipment



1. LED Anode
2. LED Cathode
3. MOSFET Drain
4. MOSFET Drain

### Absolute maximum ratings (Ambient temperature 25 °C)

Item		Symbol	Value	Units	Not
Input	Continuous LED current	$I_F$	50	mA	
	Peak LED current	$I_{FP}$	1000	mA	f=100Hz, DC 1%
	LED reverse voltage	$V_R$	5	V	
	Input power dissipation	$P_{in}$	75	mW	
Output	Load voltage	$V_L$	60	V	DC or AC peak
	Load current	$I_L$	200	mA	
	Peak load current	$I_{peak}$	600	mA	100ms(1 pulse)
	Output power dissipation	$P_{out}$	300	mW	
Total power dissipation		$P_T$	350	mW	
I/O isolation voltage		$V_{iso}$	3750	Vrms	RH 60, 1min
I/O isolation voltage(H)			5000	Vrms	RH 60, 1min
Operating temperature		$T_{opr}$	-40o +85	°C	
Storage temperature		$T_{stg}$	-40 to +100	°C	
Soldering temperature		$T_{sol}$	260	°C	10sec max.



RAPIDTEK  
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.  
<http://www.rapidtek.net>

# PHOTO DMOS RELAY

## 1 Form A Photo Relay

Electrical specifications (Ambient temperature 25 °C)							
Item		Symbol	Min.	Typ.	Max.	Units	Condition
Input	LED forward voltage	$V_F$		1.2	1.5	V	$I_F=10\text{mA}$
	Operating LED current	$I_{Fon}$		0.5	5.0	mA	
	Recover LED current	$I_{Foff}$	0.1	0.35		mA	
	Recover LED voltage	$V_{Foff}$	0.5			V	
Output	On resistance	$R_{on}$		2.0	8.0	$\Omega$	$I_F=10\text{mA}, I_L=100\text{mA}$
	Off-state leakage current	$I_{leak}$			1.0	$\mu\text{A}$	$V_L=\text{Rating}$
	Output capacitance	$C_{out}$		20		pF	$V_L=0\text{V}, f=1\text{MHz}$
Transmission	Turn on time	$T_{on}$		0.5	1.0	ms	$I_F=10\text{mA}, I_L=100\text{mA}$
	Turn off time	$T_{off}$		0.05	0.5	ms	
Coupled	I/O isolation resistance	$R_{I/O}$	$10^9$			$\Omega$	DC 500V
	I/O capacitance	$C_{I/O}$		0.8	1.5	pF	$f=1\text{MHz}$



**RAPIDTEK**  
**PHOTO DMOD RELAY**


Rapidtek Magnetic Devices Inc.  
<http://www.rapidtek.net>

# PHOTO DMOS RELAY


## 1 Form A Photo Relay

### Reference data


Load current vs. Ambient temperature




On resistance vs. Ambient temperature




Turn on time vs. Ambient temperature




Turn off time vs. Ambient temperature




LED operate current vs. Ambient temperature



LED turn off current vs. Ambient temperature




LED forward voltage vs. Ambient temperature




Voltage vs. current characteristics of output at

MOS portion




Off state leakage current vs. Load voltage

characteristics




LED forward current vs. Turn on time

characteristics




LED forward current vs. Turn off time

characteristics



Applied voltage vs. Output capacitance

characteristics




**RAPIDTEK**  
**PHOTO DMOD RELAY**

Rapidtek Magnetic Devices Inc.  
<http://www.rapidtek.net>

# PHOTO DMOS RELAY

## 1 Form A Photo Relay

### Taping specifications for surface mount devices



	$B_0$ (mm)	$F_0$ (mm)	$W_0$ (mm)
Specification	5.3±0.1	7.5±0.1	16±0.1

Package	Part No.		Packing quantity	
	Tube packing	Tape & Reel packing	Tube	Tape & Reel
DIP4	AY6E(H)	-	100pcs/1tube	-
SMD4	AY6E(H)A	AY6E(H)A-R1		1000 pcs

\*H:Option



**RAPIDTEK**  
**PHOTO DMOD RELAY**


Rapidtek Magnetic Devices Inc.  
<http://www.rapidtek.net>

# PHOTO DMOS RELAY

## 1 Form A Photo Relay


### Dimension

#### Recommended mounting pad



Unit:mm[inch]

Tolerance:±0.2[±0.007]



Unit:mm[inch]

Tolerance:±0.2[±0.007]

#### Marking

(Each photo MOS Relay shall be marked with the following information)



YY : Year, M : Monthly, W : Weeks

\*H:Option



RAPIDTEK  
PHOTO DMOD RELAY

Rapidtek Magnetic Devices Inc.  
<http://www.rapidtek.net>